



EN AW-5251 [AlMg2]

d	l +1		Nr.	
3,2	6,0	0,5 - 4,0	10.701.032.060	500
	8,0	3,5 - 6,0	10.701.032.080	500
	10,0	5,0 - 8,0	10.701.032.100	500
	12,0	7,0 - 9,0	10.701.032.120	500

dk 6,5 -0,7 **dm** 2,0 **k** 0,8 ±0,2  3,3 mm  380 N  670 N

4,0	6,0	1,0 - 3,5	10.701.040.060	500
	8,0	3,0 - 5,5	10.701.040.080	500
	10,0	5,0 - 7,0	10.701.040.100	500
	12,0	6,5 - 9,0	10.701.040.120	500
	16,0	8,5 - 12,5	10.701.040.160	500

dk 8,0 -1,0 **dm** 2,5 **k** 1,0 ±0,3  4,1 mm  740 N  1240 N

d	l +1		Nr.	
4,8	8,0	1,0 - 5,0	10.701.048.080	500
	10,0	4,0 - 7,0	10.701.048.100	500
	12,0	6,0 - 8,5	10.701.048.120	500
	14,0	8,0 - 10,5	10.701.048.140	500
	16,0	8,0 - 12,0	10.701.048.160	500
	18,0	12,5 - 14,5	10.701.048.180	500
	20,0	14,5 - 16,5	10.701.048.200	500

dk 9,5 -1,0 **dm** 2,9 **k** 1,1 ±0,3  4,9 mm  1140 N  1600 N